

SAFETY DATA SHEET

SDS ID NO.: 0191MAR019 **Revision Date** 05/27/2015

1. IDENTIFICATION

Product Name: Marathon Petroleum Marafluid 4 Transmission & Drive Train Fluid

Synonym: Marafluid 4; SAE 30 Marafluid 4; SAE 50 Marafluid 4; 10W Marafluid 4

Product Code: 0191MAR019
Chemical Family: Hydrocarbon Mixture

Recommended Use: Transmission fluid.

Restrictions on Use: All others.

Manufacturer, Importer, or Responsible Party Name and Address: MARATHON PETROLEUM COMPANY LP 539 South Main Street Findlay, OH 45840

SDS information: 1-419-421-3070 **Emergency Telephone:** 1-877-627-5463

2. HAZARD IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Acute aquatic toxicity	Category 3
Chronic aquatic toxicity	Category 3

Hazards Not Otherwise Classified (HNOC)

Not applicable.

Label elements

EMERGENCY OVERVIEW

Warning

Causes serious eye irritation Suspected of damaging fertility or the unborn child Harmful to aquatic life with long lasting effects

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train



Appearance Brown Liquid Physical State Liquid Odor Petroleum

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash hands and any possibly exposed skin thoroughly after handling

Avoid release to the environment

Precautionary Statements - Response

IF exposed or concerned: Get medical attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Not applicable.

Additional Information

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Lube oil is a complex mixture of highly refined lubricating base stocks and additives.

Composition Information:

Name	CAS Number	% Concentration
Zinc Alkyl Dithiophosphate	68649-42-3	1-5
p-Dodecvlphenol	104-43-8	0.1-1

All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First Aid Measures

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show directions

for use or safety data sheet if possible).

Inhalation: Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult,

ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If symptoms occur get medical

attention.

Skin Contact: Wash skin with plenty of soap and water. If irritation or other symptoms occur get medical

attention. Wash contaminated clothing and clean shoes before reuse. Any injection injury from high pressure equipment should be evaluated immediately by a physician as

potentially serious (See NOTES TO PHYSICIAN).

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train Page 2 of 9

Eye Contact: Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be

held away from the eveball to ensure thorough rinsing. Gently remove contacts while

flushing. Get medical attention.

Ingestion: Rinse mouth out with water. If spontaneous vomiting occurs, keep head below hips, or if

patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected

person warm and at rest. If symptoms develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse Effects: Causes eye irritation. Symptoms may include redness, itching, and inflammation. May

cause skin irritation and/or dermatitis Preexisting skin conditions and/or respiratory

disorders may be aggravated by exposure to this product.

Indication of any immediate medical attention and special treatment needed

Notes To Physician: SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material

through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

The product is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at temperatures exceeding the flash point.

Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data

Sensitivity to Mechanical Impact No. **Sensitivity to Static Discharge** No.

Special protective equipment and precautions for firefighters

Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible. Keep run-off water out of sewers and water sources.

Additional firefighting tactics

Not applicable.

NFPA Health 1 Flammability 1 Instability 0 Special Hazard -

6. ACCIDENTAL RELEASE MEASURES

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train Page 3 of 9

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Personal precautions:

Protective equipment: Use personal protection measures as recommended in Section 8.

Advise authorities and National Response Center (800-424-8802) if the product has **Emergency procedures:**

entered a water course or sewer. Notify local health and pollution control agencies, if

appropriate.

Avoid release to the environment. Avoid subsoil penetration. **Environmental precautions:**

Methods and materials for

containment:

Prevent further leakage or spillage if safe to do so.

Methods and materials for cleaning Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers.

HANDLING AND STORAGE

Safe Handling Precautions: Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists.

Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Refer to applicable EPA, OSHA, NFPA

and consistent state and local requirements.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL

EMERGENCIES (See First Aid Section 4).

Storage Conditions: Store in properly closed containers that are appropriately labeled and in a cool,

well-ventilated area. Containers that have been opened must be carefully resealed and kept

upright to prevent leakage. Store away from incompatible materials.

Strong oxidizing agents. **Incompatible Materials**

EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELS:	OSHA - Vacated PELs	NIOSH IDLH
Zinc Alkyl Dithiophosphate 68649-42-3	-	-	-	-
p-Dodecylphenol 104-43-8	-	-	-	-

Notes: The manufacturer has voluntarily elected to provide exposure limits contained in OSHA's

1989 air contaminants standard in its SDSs, even though certain of those exposure limits

were vacated in 1992.

Engineering measures: Local or general exhaust required when using at elevated temperatures that generate

vapors or mists.

Personal protective equipment

Eye protection: Use goggles or face-shield if the potential for splashing exists.

Wear neoprene, nitrile or PVA gloves to prevent skin contact. Glove suitability is based on Skin and body protection:

workplace conditions and usage. Contact the glove manufacturer for specific advice on

glove selection and breakthrough times. Wear appropriate protective clothing.

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train

Respiratory protection: Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when

there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should

be used for fire fighting.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Wash hands before breaks and immediately after handling the

product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical StateLiquidAppearanceBrown LiquidColorBrownOdorPetroleumOdor ThresholdNo data available.

Property Values (Method)
Melting Point / Freezing Point
No data available.
Initial Boiling Point / Boiling Range
No data available.

Flash Point > 200 °C / > 392 °F (Cleveland Open-Cup)

Evaporation Rate No data available. Flammability (solid, gas) Not applicable.

Flammability Limit in Air (%):

Upper Flammability Limit:
Lower Flammability Limit:
No data available.
No data available.
Vapor Pressure
Vapor Density
No data available.
No data available.
No data available.

Specific Gravity / Relative Density 0.89

Water Solubility
Solubility in other solvents
Partition Coefficient
Decomposition temperature
pH:
No data available.
No data available.
No data available.
No available data.
No data available.

Kinematic Viscosity 42-170 mm2/s @ 40°C / 104°F (ASTM D445)

Dynamic Viscosity No data available.

Explosive Properties No data available.

VOC Content (%) 1.3 (w/w)

Density

No data available.

Bulk Density

Not applicable.

10. STABILITY AND REACTIVITY

Reactivity The product is non-reactive under normal conditions.

<u>Chemical stability</u> Stable under recommended storage conditions.

<u>Possibility of hazardous reactions</u>

None under normal processing.

Hazardous polymerization Will not occur.

<u>Conditions to avoid</u> Sources of heat or ignition.

Incompatible Materials Strong oxidizing agents.

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train

Hazardous decomposition products

None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation Overheating may produce vapors which may cause respiratory irritation, dizziness and

nausea.

Eye contact Irritating to eyes. May cause reddening and tearing.

Skin contact May cause skin irritation. Prolonged or repeated exposure may cause dermatitis, folliculitis

or oil acne.

Ingestion May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Zinc Alkyl Dithiophosphate 68649-42-3	-	-	-
p-Dodecylphenol 104-43-8	-	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

This product is considered to have a low order of acute and chronic oral and dermal toxicity.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and Symptoms Causes eye irritation. Symptoms may include redness, itching, and inflammation. Contact

may cause skin dermatitis and/or irritation. Repeated or prolonged skin contact may cause

drying, reddening, itching and cracking.

Sensitization Not expected to be a skin or respiratory sensitizer.

Mutagenic effects None known.

 Carcinogenicity
 Cancer designations are listed in the table below

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Zinc Alkyl Dithiophosphate 68649-42-3	Not Listed	Not Listed	Not Listed	Not Listed
p-Dodecylphenol 104-43-8	Not Listed	Not Listed	Not Listed	Not Listed

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (STOT) - single exposure

Not classified.

Specific Target Organ Toxicity (STOT) - repeated exposure

Not classified.

Aspiration hazard Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life with long lasting effects.

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train Page 6 of 9

Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Zinc Alkyl Dithiophosphate	-	96-hr LC50 = 1-5 mg/L	-	48-hr EC50 = 1.0-1.5 mg/L
68649-42-3		Fathead minnow (static)		Daphnia magna
p-Dodecylphenol	-	96-hr LC50 = 0.14 mg/L	-	-
104-43-8		Cutthroat trout		

Persistence and degradability No information available.

Bioaccumulation Contains component(s) with the potential to bioaccumulate.

Mobility in soil No information available. No information available. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Description of Waste Residues

No information available.

Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required.

Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (49 CFR 172.101):

UN Proper Shipping Name: Not Regulated Not applicable **UN/Identification No:** Not applicable. Class: Not applicable. **Packing Group:**

TDG (Canada):

UN Proper Shipping Name: Not Regulated Not applicable. **UN/Identification No:** Not applicable. Transport Hazard Class(es): **Packing Group:** Not applicable.

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA

Chemical Inventory.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product may contain component(s) that have been listed on EPA's Extremely

Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous
	Substances and TPQs

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train

Zinc Alkyl Dithiophosphate	NA
p-Dodecylphenol	NA

SARA Section 304: This product may contain component(s) identified either as an EHS or a CERCLA

Hazardous substance which in case of a spill or release may be subject to SARA reporting

requirements:

Name	Hazardous Substances RQs
Zinc Alkyl Dithiophosphate	NA
p-Dodecylphenol	NA

SARA Section 311/312: The following EPA hazard categories apply to this product:

Acute Health Hazard

SARA Section 313: This product may contain component(s), which if in exceedance of the de minimus

threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic

Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Zinc Alkyl Dithiophosphate	1.0 % de minimis concentration
p-Dodecylphenol	None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Zinc Alkyl Dithiophosphate

Louisiana Right-To-Know:

California Proposition 65:

New Jersey Right-To-Know:

Not Listed

Not Listed

Not Jisted

Pennsylvania Right-To-Know: Environmental hazard

Massachusetts Right-To Know:

Florida Substance List:

Rhode Island Right-To-Know:

Not Listed

Not Listed

Michigan Critical Materials Register List: 100 lb Annual usage threshold

Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous
Not Listed
Not Listed

Substances:

New Jersey - Special Hazardous Substances: Not Listed

New Jersey - Environmental Hazardous SN 3012 TPQ: 500 lb (Category Code N982. Includes any Substances List: unique chemical substance that contains the named metal as

part of that chemical structure)

Illinois - Toxic Air Contaminants: Not Listed New York - Reporting of Releases Part 597 - Not Listed

List of Hazardous Substances:

p-Dodecylphenol

Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: Not Listed Pennsylvania Right-To-Know: Not Listed Massachusetts Right-To Know: Not Listed Florida Substance List: Not Listed Rhode Island Right-To-Know: Not Listed Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances:

New Jersey - Special Hazardous Substances:
New Jersey - Environmental Hazardous
Not Listed
Not Listed

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train

Substances List:

Illinois - Toxic Air Contaminants:

New York - Reporting of Releases Part 597
Not Listed

List of Hazardous Substances:

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL)

or are exempt.

Canadian Regulatory Information: This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations and the SDS contains all of the information required by those

regulations.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Zinc Alkyl Dithiophosphate	D2B	1%



Note: Not applicable.

16. OTHER INFORMATION

Prepared By Toxicology and Product Safety

Revision Notes

Revision Date 05/27/2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS ID NO.: 0191MAR019 Product name: Marathon Petroleum Marafluid 4 Transmission & Drive Train