



Safety Data Sheet

Section 1: Identification

Product identifier

Product Name

- **No. 1 Ultra Low Sulfur Diesel 15ppm Sulfur Max with 6-20% Biodiesel**

Synonyms

- No. 1 Diesel with Biodiesel B2 Blend 15 ppm Sulfur Max; No. 1 Diesel with Biodiesel B5 Blend 15 ppm Sulfur Max; Ultra Low Sulfur No. 1 Diesel with B2 Biodiesel; Ultra Low Sulfur No. 1 Diesel with B5 Biodiesel

SDS Number/Grade

- 0031NOR001

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

- Vehicle fuel

Details of the supplier of the safety data sheet

Manufacturer

- Northern Tier Energy
301 St. Paul Park Road
St. Paul Park, MN 55071
United States
www.ntenergy.com

Telephone (General) • 651-459-9771

Emergency telephone number

Chemtrec

- 800-424-9300

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 3
Aspiration 1
Skin Irritation 2
Eye Irritation 2A
Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Carcinogenicity 2

Label elements

OSHA HCS 2012

DANGER



- Hazard statements** • Flammable liquid and vapour
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of causing cancer.

Precautionary statements

- Prevention** • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
Keep container tightly closed.
Ground and/or bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing mists, vapours, and/or spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, clothing , and eye/face protection , .
- Response** • In case of fire: Use appropriate media for extinction.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If on skin: Wash with plenty of water .
Take off contaminated clothing and wash before reuse.
Specific treatment, see supplemental first aid information.
If skin irritation occurs: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Do NOT induce vomiting.
IF exposed or concerned: Get medical advice/attention.
- Storage/Disposal** • Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

- OSHA HCS 2012** • Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.
-

Canada

According to: WHMIS

Classification of the substance or mixture

- WHMIS** • Combustible Liquids - B3
Other Toxic Effects - D2B

Label elements

WHMIS



- Combustible Liquids - B3
Other Toxic Effects - D2B

Other hazards

- WHMIS** • In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).
-

Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Kerosene	CAS:8008-20-6	80% TO 94%	Ingestion/Oral-Rabbit LD50 • 2835 mg/kg Inhalation-Rat LC50 • >5000 mg/m ³ 4 Hour (s) Skin-Rabbit LD50 • >2000 mg/kg	OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2A; Asp. Tox. 1; STOT SE 3: Narc.	NDA
Soybean oil, Methyl ester	CAS:67784-80-9	0% TO 20%	NDA	OSHA HCS 2012: Not Classified	NDA
Fatty acids, tallow, methyl esters	CAS:61788-61-2	0% TO 20%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Rapeseed derived)	CAS:73891-99-3	0% TO 20%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Fatty Acid, Methyl Ester)	CAS:68937-84-8	0% TO 20%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Canola derived)	CAS:129828-16-6	0% TO 20%	NDA	OSHA HCS 2012: Not Classified	NDA
Naphthalene	CAS:91-20-3	0.01% TO 0.5%	Skin-Rabbit LD50 • >20 g/kg Ingestion/Oral-Rat LD50 • 490 mg/kg	OSHA HCS 2012: Flam. Sol. 2; Acute Tox. 4 (orl); Skin Irrit. 2; Muta. 2; Carc. 2; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (Blood, Eyes, Or, Inhl)	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention if symptoms occur.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water. If irritation develops and persists, get medical attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do NOT induce vomiting. Obtain medical attention immediately if ingested.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media**
- For small fires, Class B fire extinguishing media such as CO₂, dry chemical, foam (AFFF/ATC) or water spray.
For large fires, water spray, fog or foam (AFFF/ATC)

Unsuitable Extinguishing Media

- Avoid using straight water streams.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- **HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products

- No data available

Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. **LARGE FIRES:** Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. **LARGE SPILL:** Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded.
 LARGE SPILLS: Dike far ahead of liquid spill for later disposal.
 LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

- Use only in well ventilated areas. Avoid contact with heat and ignition sources. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Never siphon this product by mouth. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage

- Keep container tightly closed. Store in appropriately labeled containers. Store in a cool/low-temperature, well-ventilated place.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Naphthalene (91-20-3)	TWAs	10 ppm TWA	10 ppm TWA; 50 mg/m ³ TWA	10 ppm TWA; 50 mg/m ³ TWA
	STELs	Not established	15 ppm STEL; 75 mg/m ³ STEL	Not established
Kerosene (8008-20-6)	TWAs	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol exposures, total hydrocarbon vapor)	100 mg/m ³ TWA	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face

- Wear safety goggles.

Skin/Body

- Wear appropriate gloves.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Clear to amber liquid.
Color	Amber	Odor	No data available
Odor Threshold	No data available		
General Properties			
Boiling Point	400 to 640 F(204.4444 to 337.7778 C)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	= 0.8 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	1 to 10 mmHg (torr) @ 100 F (37.7778 C)	Vapor Density	4 to 5 Air=1
Evaporation Rate	No data available	VOC (Wt.)	10 %
VOC (Vol.)	10 %		
Flammability			
Flash Point	130 to 190 F(54.4444 to 87.7778 C)	UEL	5 %
LEL	0.7 %	Autoignition	637 F(336.1111 C)
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity**Reactivity**

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Excessive heat, sources of ignition and open flames.

Incompatible materials

- Strong oxidizers such as nitrates, perchlorates, chlorine, fluorine.

Hazardous decomposition products

- Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

Section 11 - Toxicological Information**Information on toxicological effects**

Components		
Kerosene (80% TO 94%)	8008-20-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 15 g/kg; <i>Skin and Appendages:After topical exposure:Corrosive;</i> Irritation: Skin-Rabbit • 500 mg • Severe irritation
		Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDLo • 158 mg/kg; <i>Brain and</i>

Naphthalene (0.01% TO 0.5%)	91-20-3	<p>Coverings:Other degenerative changes; Liver:Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport; Inhalation-Human TClO • 250 mg/m³; Sense Organs and Special Senses:Eye:Lacrimation; Behavioral:Headache; Skin-Rabbit LD50 • >20 g/kg; Unreported-Guinea Pig LD50 • 1200 mg/kg; Behavioral:Somnolence (general depressed activity);</p> <p>Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation;</p> <p>Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 500 mg/kg 10 Day(s)-Intermittent; Behavioral:Sleep; Lungs, Thorax, or Respiration:Dyspnea; Ingestion/Oral-Rat TDLo • 4500 mg/kg 10 Day(s)-Intermittent; Brain and Coverings:Other degenerative changes;</p> <p>Mutagen: Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L;</p> <p>Reproductive: Ingestion/Oral-Mouse TDLo • 2400 mg/kg (7-14D preg); Reproductive Effects:Effects on Newborn:Live birth index; Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive); Ingestion/Oral-Rat TDLo • 4500 mg/kg (6-15D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities;</p> <p>Tumorigen / Carcinogen: Inhalation-Mouse TClO • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Inhalation-Rat TClO • 1575 mg/kg 105 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors; Inhalation-Rat TClO • 60 ppm 6 Hour(s) 105 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors</p>
-----------------------------------	---------	--

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • Eye Irritation 2A
Acute toxicity	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 2
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Toxicity for Reproduction	OSHA HCS 2012 • No data available
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available

Potential Health Effects

Inhalation

- Acute (Immediate)**
 - May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- Chronic (Delayed)**
 - No data available.

Skin

- Acute (Immediate)**
 - Causes skin irritation.
- Chronic (Delayed)**
 - No data available.

Eye

- Acute (Immediate)**
 - Causes serious eye irritation.
- Chronic (Delayed)**
 - No data available.

Ingestion

- Acute (Immediate)**
 - Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- Chronic (Delayed)**
 - No data available.

Carcinogenic Effects

- Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
Naphthalene	91-20-3	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information**Toxicity**

- Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

- Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

- Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

- Non-mandatory section - information about this substance not complied for this reason.

Other adverse effects

- Non-mandatory section - information about this substance not complied for this reason.

Section 13 - Disposal Considerations**Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	NA1993	Fuel oil (No. 1)	3	III	
TDG	1202	DIESEL FUEL	3	III	

Special precautions for user

- None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

Inventory				
Component	CAS	Canada DSL	Canada NDSL	TSCA
Biodiesel (Canola derived)	129828-16-6	Yes	No	Yes
Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Yes	No	Yes
Biodiesel (Rapeseed derived)	73891-99-3	Yes	No	Yes
Fatty acids, tallow, methyl esters	61788-61-2	Yes	No	Yes
Kerosene	8008-20-6	Yes	No	Yes
Naphthalene	91-20-3	Yes	No	Yes
Soybean oil, Me ester	67784-80-9	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	B4, D2A
• Kerosene	8008-20-6	B3, D2B
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Canada - WHMIS - Ingredient Disclosure List

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	1 %
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Environment

Canada - CEPA - Priority Substances List

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	100 lb final RQ; 45.4 kg final RQ
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed

• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	0.1 % de minimis concentration
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	carcinogen, initial date 4/19/02
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed

• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed
U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)		
• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	5.8 µg/day NSRL
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Other Information

- **WARNING:** This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date	• 08/October/2015
Preparation Date	• 13/July/2015
Disclaimer/Statement of Liability	• Please provide.

Key to abbreviations

NDA = No data available