



Safety Data Sheet

Section 1: Identification

Product identifier

Product Name

- **No. 1 Ultra Low Sulfur Diesel 15ppm Sulfur Max with 2-5% Biodiesel**

Synonyms

- No. 1 Diesel with Biodiesel B2 Blend 15 ppm Sulfur Max; No. 1 Diesel with Biodiesel B5 Blend 15 ppm Sulfur Max; Nordic Diesel; Premium Diesel; Ultra Low Sulfur No. 1 Diesel with B2 Biodiesel; Ultra Low Sulfur No. 1 Diesel with B5 Biodiesel;

SDS Number/Grade

- 0022NOR001

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

- Vehicle fuel

Details of the supplier of the safety data sheet

Manufacturer

- Northern Tier Energy
301 St. Paul Park Road
St. Paul Park, MN 55071
United States
www.ntenergy.com

Telephone (General) • 651-459-9771

Emergency telephone number

Chemtrec

- 800-424-9300

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 3
Aspiration 1
Skin Irritation 2
Eye Irritation 2A
Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Carcinogenicity 2
Reproductive Toxicity 1B

Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Flammable liquid and vapour
 - May be fatal if swallowed and enters airways
 - Causes skin irritation
 - Causes serious eye irritation
 - May cause drowsiness or dizziness
 - Suspected of causing cancer.
 - May damage fertility or the unborn child.

Precautionary statements

- Prevention**
- Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - Keep container tightly closed.
 - Ground and/or bond container and receiving equipment.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Avoid breathing mists, vapours, and/or spray.
 - Wash thoroughly after handling.
 - Use only outdoors or in a well-ventilated area.
 - Wear protective gloves, clothing, and eye/face protection, .

- Response**
- In case of fire: Use appropriate media for extinction.
 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - Call a POISON CENTER or doctor/physician if you feel unwell.
 - If on skin: Wash with plenty of water .
 - Take off contaminated clothing and wash before reuse.
 - Specific treatment, see supplemental first aid information.
 - If skin irritation occurs: Get medical advice/attention.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - If eye irritation persists: Get medical advice/attention.
 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 - Do NOT induce vomiting.
 - IF exposed or concerned: Get medical advice/attention.

- Storage/Disposal**
- Store in a well-ventilated place. Keep container tightly closed.
 - Keep cool.
 - Store locked up.
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

WHMIS

- Combustible Liquids - B3
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

Label elements

WHMIS



- Combustible Liquids - B3
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Kerosene	CAS:8008-20-6	95% TO 98%	Ingestion/Oral-Rat LD50 • 15 g/kg Inhalation-Rat LC50 • >5000 mg/m ³ 4 Hour(s) Skin-Rabbit LD50 • >2000 mg/kg	OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2A; Asp. Tox. 1; STOT SE 3: Narc.	NDA
Soybean oil, Me ester	CAS:67784-80-9	0% TO 5%	NDA	OSHA HCS 2012: Not Classified	NDA
Fatty acids, tallow, methyl esters	CAS:61788-61-2	0% TO 5%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Rapeseed derived)	CAS:73891-99-3	0% TO 5%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Fatty Acid, Methyl Ester)	CAS:68937-84-8	0% TO 5%	NDA	OSHA HCS 2012: Not Classified	NDA
Biodiesel (Canola derived)	CAS:129828-16-6	0% TO 5%	NDA	OSHA HCS 2012: Not Classified	NDA
Naphthalene	CAS:91-20-3	0.010027% TO 0.50055%	Skin-Rabbit LD50 • >20 g/kg Ingestion/Oral-Rat LD50 • 490 mg/kg	OSHA HCS 2012: Flam. Sol. 2; Acute Tox. 4 (orl); Skin Irrit. 2; Muta. 2; Carc. 2; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (Blood, Eyes, Orl, Inhl)	NDA
Xylene	CAS:1330-20-7	0.13266% TO 0.19899%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (inh); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.	NDA
Ethylbenzene	CAS:100-41-4	0.03312% TO 0.04968%	Ingestion/Oral-Rat LD50 • 3500 mg/kg Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s) Skin-Rabbit LD50 •	OSHA HCS 2012: Exposure limits	NDA

1,2,4-Trimethylbenzene	CAS:95-63-6	0.00027% TO 0.00275%	>5000 mg/kg Ingestion/Oral-Rat LD50 • 5 g/kg Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour (s)	OSHA HCS 2012: Exposure limits	NDA
Toluene	CAS:108-88-3	0.00018% TO 0.00243%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	OSHA HCS 2012: Exposure limits	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention if symptoms occur.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water. If irritation develops and persists, get medical attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do NOT induce vomiting. Obtain medical attention immediately if ingested.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media

- For small fires, Class B fire extinguishing media such as CO₂, dry chemical, foam (AFFF/ATC) or water spray.
For large fires, water spray, fog or foam (AFFF/ATC)

Unsuitable Extinguishing Media

- Avoid using straight water streams.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products

- No data available

Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal. LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

- Use only in well ventilated areas. Avoid contact with heat and ignition sources. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Never siphon this product by mouth. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage

- Keep container tightly closed. Store in appropriately labeled containers. Store in a cool/low-temperature, well-ventilated place.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines			
Result	ACGIH	NIOSH	OSHA
Ceilings	Not established	Not established	300 ppm Ceiling

Toluene (108-88-3)	TWAs	20 ppm TWA	100 ppm TWA; 375 mg/m3 TWA	200 ppm TWA
	STELs	Not established	150 ppm STEL; 560 mg/m3 STEL	Not established
1,2,4-Trimethylbenzene (95-63-6)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established
Naphthalene (91-20-3)	TWAs	10 ppm TWA	10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA; 50 mg/m3 TWA
	STELs	Not established	15 ppm STEL; 75 mg/m3 STEL	Not established
Ethylbenzene (100-41-4)	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established
Xylene (1330-20-7)	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
	STELs	150 ppm STEL	Not established	Not established
Kerosene (8008-20-6)	TWAs	200 mg/m3 TWA (application restricted to conditions in which there are negligible aerosol exposures, total hydrocarbon vapor)	100 mg/m3 TWA	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face

- Wear safety goggles.

Skin/Body

- Wear appropriate gloves.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
 NIOSH = National Institute of Occupational Safety and Health
 OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures
 TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Clear to amber liquid.
Color	Clear to amber.	Odor	No data available
Odor Threshold	No data available		
General Properties			
Boiling Point	360 to 550 F(182.2222 to 287.7778 C)	Melting Point	No data available
Decomposition Temperature	No data available	pH	Neutral
Specific Gravity/Relative Density	= 0.8 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		

Volatility

Vapor Pressure	1 to 10 mmHg (torr) @ 100 F (37.7778 C)	Vapor Density	4.5 Air=1
Evaporation Rate	No data available	VOC (Wt.)	10 %
VOC (Vol.)	10 %		

Flammability

Flash Point	120 to 190 F(48.8889 to 87.7778 C)	UEL	5 %
LEL	0.7 %	Autoignition	489 F(253.8889 C)
Flammability (solid, gas)	No data available		

Environmental

Octanol/Water Partition coefficient	No data available		
-------------------------------------	-------------------	--	--

Section 10: Stability and Reactivity**Reactivity**

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Excessive heat, sources of ignition and open flames.

Incompatible materials

- Strong oxidizers such as nitrates, chlorates, Peroxides.

Hazardous decomposition products

- Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

Section 11 - Toxicological Information**Information on toxicological effects**

Components		
Kerosene (95% TO 98%)	8008-20-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 15 g/kg; <i>Skin and Appendages:After topical exposure:Corrosive;</i> Irritation: Skin-Rabbit • 500 mg • Severe irritation
Naphthalene (0.010027% TO 0.50055%)	91-20-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDLo • 158 mg/kg; <i>Brain and Coverings:Other degenerative changes; Liver:Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport; Inhalation-Human TCLo • 250 mg/m³; Sense Organs and Special Senses:Eye: Lacrimation; Behavioral:Headache;</i> Skin-Rabbit LD50 • >20 g/kg; Unreported-Guinea Pig LD50 • 1200 mg/kg; <i>Behavioral:Somnolence (general depressed activity);</i> Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 500 mg/kg 10 Day(s)-Intermittent; <i>Behavioral:Sleep; Lungs, Thorax, or Respiration:Dyspnea;</i> Ingestion/Oral-Rat TDLo • 4500 mg/kg 10 Day(s)-Intermittent; <i>Brain and Coverings:Other degenerative changes;</i> Mutagen: Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L; Reproductive: Ingestion/Oral-Mouse TDLo • 2400 mg/kg (7-14D preg); <i>Reproductive Effects:Effects on Newborn:Live birth index; Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive);</i> Ingestion/Oral-Rat TDLo • 4500 mg/kg (6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities;</i>

		Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors</i> ; Inhalation-Rat TCLo • 1575 mg/kg 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors</i> ; Inhalation-Rat TCLo • 60 ppm 6 Hour(s) 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors</i>
Xylene (0.13266% TO 0.19899%)	1330- 20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; <i>Liver:Other changes; Kidney, Ureter, and Bladder:Other changes</i> ; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Man LCLo • 10000 ppm 6 Hour(s); <i>Behavioral:General anesthetic; Lungs, Thorax, or Respiration:Cyanosis; Blood:Other changes</i> ; Inhalation-Human TCLo • 200 ppm; <i>Sense Organs and Special Senses:Olfaction:Other changes; Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Other changes</i> ; Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Rabbit TCLo • 1 g/m ³ 24 Hour(s)(7-20D preg); <i>Reproductive Effects:Effects on Fertility:Abortion</i> ; Inhalation-Rat TCLo • 50 mg/m ³ 6 Hour(s)(1-21D preg); <i>Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue)</i>

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 2
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Toxicity for Reproduction	OSHA HCS 2012 • Toxic to Reproduction 1B
Respiratory sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • Eye Irritation 2A

Potential Health Effects

Inhalation

- Acute (Immediate)**
 - May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- Chronic (Delayed)**
 - No data available.

Skin

- Acute (Immediate)**
 - Causes skin irritation.
- Chronic (Delayed)**
 - No data available.

Eye

- Acute (Immediate)**
 - Causes serious eye irritation.
- Chronic (Delayed)**
 - No data available.

Ingestion

- Acute (Immediate)**
 - Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- Chronic (Delayed)**
 - No data available.

Carcinogenic Effects

- Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
Naphthalene	91-20-3	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
Ethylbenzene	100-41-4	Group 2B-Possible Carcinogen	Not Listed

Reproductive Effects

- Repeated and prolonged exposure may cause reproductive effects.

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information**Toxicity**

- Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

- Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

- Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

- Non-mandatory section - information about this substance not complied for this reason.

Other adverse effects

- Non-mandatory section - information about this substance not complied for this reason.

Section 13 - Disposal Considerations**Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	NA1993	Fuel oil (No. 1)	3	III	NDA
	UN1202	Fuel oil (No. 1)	3	III	NDA
TDG	UN1202	FUEL OIL	3	III	NDA

Special precautions for user

- None specified.

Transport in bulk according

- No data available

to Annex II of MARPOL 73/78
and the IBC Code

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

Inventory				
Component	CAS	Canada DSL	Canada NDSL	TSCA
1,2,4-Trimethylbenzene	95-63-6	Yes	No	Yes
Biodiesel (Canola derived)	129828-16-6	Yes	No	Yes
Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Yes	No	Yes
Biodiesel (Rapeseed derived)	73891-99-3	Yes	No	Yes
Ethylbenzene	100-41-4	Yes	No	Yes
Fatty acids, tallow, methyl esters	61788-61-2	Yes	No	Yes
Kerosene	8008-20-6	Yes	No	Yes
Naphthalene	91-20-3	Yes	No	Yes
Solvent naphtha (petroleum), light aromatic	64742-95-6	Yes	No	Yes
Soybean oil, Me ester	67784-80-9	Yes	No	Yes
Toluene	108-88-3	Yes	No	Yes
Xylene	1330-20-7	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	B4, D2A
• Ethylbenzene	100-41-4	B2, D2A, D2B
• Toluene	108-88-3	B2, D2A, D2B
• Xylene	1330-20-7	B2, D2A, D2B
• 1,2,4-Trimethylbenzene	95-63-6	B3
• Solvent naphtha (petroleum), light aromatic	64742-95-6	B3, D2B
• Kerosene	8008-20-6	B3, D2B
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Canada - WHMIS - Ingredient Disclosure List

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	1 %
• Ethylbenzene	100-41-4	0.1 %

• Toluene	108-88-3	1 %
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	0.1 %
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Environment

Canada - CEPA - Priority Substances List

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Priority Substance List 1 (substance not considered toxic)
• Xylene	1330-20-7	Priority Substance List 1 (substance not considered toxic)
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed

• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	
• Ethylbenzene	100-41-4	(listed under Ethyl benzene)
• Toluene	108-88-3	
• Xylene	1330-20-7	(isomers and mixtures)
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	100 lb final RQ; 45.4 kg final RQ
• Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg final RQ
• Toluene	108-88-3	1000 lb final RQ; 454 kg final RQ
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	0.1 % de minimis concentration
• Ethylbenzene	100-41-4	0.1 % de minimis concentration
• Toluene	108-88-3	1.0 % de minimis concentration
• Xylene	1330-20-7	1.0 % de minimis concentration
• 1,2,4-Trimethylbenzene	95-63-6	1.0 % de minimis concentration
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed

• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	carcinogen, initial date 4/19/02
• Ethylbenzene	100-41-4	carcinogen, initial date 6/11/04
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	developmental toxicity, initial date 1/1/91
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	7000 µg/day MADL (level represents absorbed dose)
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
--------------------------------------	------------	------------

• Naphthalene	91-20-3	5.8 µg/day NSRL
• Ethylbenzene	100-41-4	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Fatty acids, tallow, methyl esters	61788-61-2	Not Listed
• Naphthalene	91-20-3	Not Listed
• Ethylbenzene	100-41-4	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• Kerosene	8008-20-6	Not Listed
• Soybean oil, Me ester	67784-80-9	Not Listed
• Biodiesel (Rapeseed derived)	73891-99-3	Not Listed
• Biodiesel (Canola derived)	129828-16-6	Not Listed
• Biodiesel (Fatty Acid, Methyl Ester)	68937-84-8	Not Listed

Other Information

- **WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Section 16 - Other Information

Last Revision Date	• 22/June/2015
Preparation Date	• 30/November/2010
Disclaimer/Statement of Liability	• Please provide.

Key to abbreviations

NDA = No data available
